




129.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Hi3798M processor !
- SATA HDD support !
- ONVIF ! PTZ !
- H.264/H.265 !



Support:  [Manual \[EN\]](#)

CTFNVR-1 is a digital video recorder for IP-cameras (Signal transmission over LAN or the integrated 8x POE-LAN-connectors). CTFNVR-1 supports the modern H.265 compression. The recorder allows simultaneous multi-channel real-time recording, playback. For recordings you can integrate a SATA HDD (up to 8TB).

**Features:**

- Support HDMI 4K output
- Support web, CMS, center platform management software XMEYE

- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G,WIFI,IP searches etc.)
- Visit remotely,built-in ARSP,achieve start up by one step

**Specification:**

Main processor : Hi3798M

Operating System : Embedded Linux

System Resources : Simultaneous multi-channel real-time recording, playback, network operation, USB backup

Operator interface :16-bit true color graphic menu operation interface, support

USB mouse operation

Preview : 1/4/8/16

Video input (IP) : 4\*5M/8\*4M/8\*3M/16\*960P

Video standards : PAL(625TVL,50f/s);NTSC(525TVL,60f/s)

Video compression H.265/H.264

Display quality Max:4K

Playback quality : 5M/4M/3M/960P

Decode : 2\*5M/4\*4M/4\*3M/4\*960P

Motion detection : Yes

Audio compression :G.711A

Recording mode :Manual>Alarm>Video Detection>Continuous

Local Playback :2\*5M/4\*4M/4\*3M/4\*960P

Search mode search by Time/calendar/event/channel

Record Storage :HDD ,network

Backup mode : Network backup, USB hard disk, USB burner, SATA burner

Video output : 1ch HDMI HD output(can be extended to support VGA)

Network interface : 1\* 10M/100M Adaptive Ethernet port,8 POE ports

USB interface :2\*USB 2.0 port

Hard disk Port: 1\*SATA(Up to 8TB

) PTZ control :Control PTZ device by network

ONVIF : Support

PoE Standard :IEEE802.3af With 15.4W Output Each Port

Power supply : 48V/2.5A

Net weight : 1.75KG

Gross Weight : 2.03KG

Dimension :26CM\*24CM\*5CM