

999.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Intel Kabylake-U SoC !



- Intel® 7th Gen. SoC Processors
- 2 \* SO-DIMM Dual CH DDR4 2133MHz up to 32GB
- 4 \* USB2.0, 4 \* USB3.0, 2 \* COM, 1 \* DP, 1 \* HDMI, 2 \* RJ45, 1 \* Line out
- Mainboard: JNF632N-7200U with i5-7200U SoC CPU

|                 |                                                     |                      |                        |
|-----------------|-----------------------------------------------------|----------------------|------------------------|
| M/B Model       | – JNF632N-7200U / 3.5" SBC                          |                      |                        |
| Part No         | Non-Wifi                                            | Mini PCIe b/g/n Wifi | Mini PCIe ac Wifi card |
|                 | – HBJC513F632-72B (Default)                         | – HBJC513F632W-72B   | – HBJC513F632Z-72B     |
| BIOS            | – AMI 64MB SMT Flash ROM                            |                      |                        |
| CPU/Chipset     | – Intel® Kabylake i5-7200U SoC Processor (15W)      |                      |                        |
| Storage         | – 1 * 2.5" SATAIII 6Gb/s internal drive bay         |                      |                        |
|                 | – 1 * Full-size mSATA/Mini-PCI Express shared slot  |                      |                        |
| Network         | – 1 * Intel i211AT, 1 * Intel i219LM GbE            |                      |                        |
|                 | – 1 * half-size Mini-PCIe slot (for WiFi expansion) |                      |                        |
| Rear Panel I/O  | – 4 * USB 3.0 ports                                 |                      |                        |
|                 | – 2 * USB 2.0 ports                                 |                      |                        |
| Rear Panel I/O  | – 1 * HDMI 1.4 (Max. Resolution: 4096*2160@60Hz)    |                      |                        |
|                 | – 1 * DP1.2 (Max. Resolution: 4096*2304@60Hz)       |                      |                        |
| Rear Panel I/O  | – 2 * RJ45                                          |                      |                        |
|                 | – 1 * Line-out                                      |                      |                        |
| Rear Panel I/O  | – 2 * COM (COM1 support RS232/422/485)              |                      |                        |
|                 | – 2 * Antenna holes (WiFi only)                     |                      |                        |
| Rear Panel I/O  | – 1 * DC-in Jack                                    |                      |                        |
|                 | – 1 * Power button, 1 * Reset button                |                      |                        |
| Front Panel I/O | – 1 * Power LED, 1 * HDD LED                        |                      |                        |
|                 | – 2 * USB 2.0 ports                                 |                      |                        |
| Front Panel I/O | – 1 * Line-out, 1 * MIC                             |                      |                        |
|                 | – AC-DC Adapter_DC12V_5A_60W                        |                      |                        |
| Power Source    | – AC 90~240V input                                  |                      |                        |
| Compliance      | – CE, FCC, RoHS, ErP Ready                          |                      |                        |

|             |                                                                                                                                                                 |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Temperature | <ul style="list-style-type: none"><li>– Operating Temperature: 0 ~ 50° C</li><li>– Storage Temperature: -20 ~ 85° C</li></ul>                                   |
| Dimensions  | <ul style="list-style-type: none"><li>– 264 (W) x 199.4 (D) x 38 (H) mm</li></ul>                                                                               |
| Packing     | <ul style="list-style-type: none"><li>– Net Weight: 2.4KG</li><li>– Gross Weight: 3.4KG</li><li>– Color Box dimension: 406 (W) * 148 (D) * 380 (H) mm</li></ul> |
| OS Support  | <ul style="list-style-type: none"><li>– Windows 10, Linux</li></ul>                                                                                             |