

198.00 EUR
incl. 19% VAT, plus [shipping](#)

- Pico-ITX
- SATA
- DDR-II !
- 1 Ghz CPU



Model	VIA EPIA PX10000G
Processor	VIA C7 1.0 GHz - Socket NanoBGA2
Chipset	VIA VX700 Unified Digital Media GCP Chipset
System Memory	1 DDR2 512 SDRAM socket Up to 1GB memory size
ISA	Integrated VIA UniChrome Pro 3 3D2D AGP graphics with MPEG-2/4 and WMV9 decoding acceleration

Onboard IDE	1 UltraDMA 133/100/66 connector (2 Drive 64 pin header)
Onboard Serial ATA	1 SATA connector
Onboard LAN	1 VIA VT6105G 10/100Mbps Ethernet controller with Power Management System
Onboard Audio	VIA VT1708A High Definition Audio Codec
Internal I/O Connectors	4 USB pin headers for 4 USB 2.0 ports • 1 COM port connector • 1 PS2 mouse/keyboard pin header • 1 LVDS/DVI connector • 1 Multimedia connector to support external TV-out interface, Video capture port interface and Low pin count interface • 1 Audio pin header for line-out, line-in, mic-in, S/PDIF in, and 7.1 channels audio output • 1 Fan pin header for CPU fan • 1 Pico-ITX power connector
External I/O Ports	1 RJ-45 LAN port • 1 VGA port
BIOS	Award BIOS • 4/8Mbit flash memory
Management	CPU temperature reading (manufacturing option) • Watch Dog Timer (manufacturing option) • Keyboard-Power-on, Timer-Power-on • Wake-on-LAN • System power management • AC power failure recovery
Operating Temperature	0°C ~ 50°C
Operating Humidity	20% ~ 95% (relative humidity, non-condensing)
Form Factor	• Pico-ITX 10 cm x 7.2 cm